


Mimio DS Series 65”

Product# DS650



The Mimio DS Series delivers powerful brilliance with effortless control. This large format professional display is a complete digital signage solution and sized perfectly to fit any classroom, hallway, meeting room, or office space.

Product Features

- Ultra-narrow edge metallic appearance
- 4K Ultra HD display
- AI PQ Scene Recognition
- Portrait and Landscape
- Screen Splicing
- Support wireless screen-sharing
- Support the network wake-up function
- Support serial command
- Support dual network port
- Wall hanging / scaffolding can be adapted to various installation requirements
- Large memory and storage of 3G/32G

Display Specifications	
Size Options	65"
Panel Type	VA
Response Time	8ms
Aspect Ratio	16:9
Display Area (HxV)	1428.48 x 803.52mm
Pixel Pitch (HxV)	0.372 × 0.372mm
Resolution (HxV)	3840 x 2160
Refreshing Frequency	60Hz
Display Color	1.07B (10bit)
NTSC	72%
Contrast Ratio	1200:1
Viewing Angle	178°
Back Light Unit	DLED
Brightness with glass (min)	400cd/m ²
Brightness with glass (typ)	450cd/m ²
Lifetime	≥50000 Hours

Operating System	
System Version	Android 11.00
RAM	4GB
ROM	32GB
CPU	A55*4
GPU	MaliG52 MP2
Audio	
Sound Channel	2.0
Speaker Power	2 × 10W
Sound Pressure Level	81dB
Peak Power	54W
Power	
Power Requirements	100-240V~50/60Hz
Typical Power* [1]	165W
Max Power* [2] (W/OPS)	335W
Peak Power	≤0.5W
i/o Port	
HDMI IN (2 Ports)	Up to 4K@60Hz, HDCP 2.1, CEC, ARC (HDMI 1)
HDMI Out (1 Port)	(HDMI Daisy chain, up to 3*3) Follow HDMI IN; Android channel do not support
USB 2.0 (1 Port)	For system upgrades
USB 3.0 (1 Port)	External U disk, mouse, and other peripherals



by Boxlight®

USB Type-C (1 Port)	Video, Audio, External Type-C U disk
Audio Out (1 Port)	3.5mm Phone Jack
SPDIF (1 Port)	PCM Output Format
RS232 (1 Port)	Baud Rate 9600
LAN RJ45 IN (1 Port)	10M/100M/1000Mbps

Physical Specifications

Dimension (L×H×D)	1463.3 × 838 × 81.6mm
Dimension (package) L×W×H	1628 x 208 x 942mm
Thickness of machine & wall mount	101.4mm (WIB9080A)
Wall-hanging Screw Spec	M8 × 25mm
VESA	600 × 400mm
Net Weight (kg) Weight (lb)	25.40 60
Gross Weight (kg) Weight (lb)	33.25 73.30
OPS Slot	Yes, 80 Pin OPS

Accessories

Power Cord	1
Remote Control	1
Batteries for Remote	2

Environmental Conditions	
Operation Temperature	0°C~40°C
Operation Humidity	10%~90%RH
Storage Temperature	-20°C~60°C
Storage Humidity	10%~90%RH
Altitude	Below 5000 meters
Standard Module	
Wireless Module	MP4-WIFI-MOD

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product.

The product images are for illustrative purposes only and may slightly differ in appearance, color, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.